



LINGJACK

林傑

PORTABLE FIRE EXTINGUISHER

4KG ABC STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-4ASE

Specification :

- Capacity : 4 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Fire Rating : 21A,144B,C
- Class of Fire : A,B,C
- Discharge Time : 16.33 sec
- Discharge Range : 5 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Hose Length : 440 mm
- Size : Dia. 139 x 465(H) mm
- Gross Weight (Approx.) : 6.5 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Effective Suppression of Class A,B & C Fires


Standards : Manufactured in accordance with EN 3-7:2004+A1:2007

Approvals : LPCB (UK), Wheel Mark (MED), CE Mark (PED)

Origin : Made in Singapore



EN3-7:2004 + A1:2007
Cert No. 501a



0832



0832

GOOD QUALITY GREAT SERVICES

www.lingjack.com